



KOKA 99 HD Plus PVC wh250m reel

Art. Number 151702



KOKA 99 HD Plus PVC white 250m reel

CPR compliant - Fire class Eca according to the EN50575 fire standard

TRIAX KOKA 99 HD Plus PVC type is a premium cable for indoor installations. The wide frequency range allows transmission of digital signals in both Cable-tv networks, Satellite antenna systems and Terrestrial antenna installations.

This cable is designed with a center conductor of bare copper (Cu) which offers high performance even over long distances. Due to the gas injected foam, which is far superior to the chemical foam, the copper conductor carries the signals without great losses. High shielding Class A means less problems with disturbances from external electronic devices and thereby a clear tv-picture.

Technical Specifications

ORDER INFORMATION

EAN Number 5702661517020

CONSTRUCTION

Dielectric - dimension mm	4.57 ± 0.1 mm
Dielectric - material	Foam PE
1. Shield foil – material	Alu/PET/Alu bonded
1. Shield foil - overlap %	20 %
Inner conductor - dimension mm	1.02 ± 0.01 mm
Inner conductor - material	Cu
Jacket – dimension mm	6.9 ± 0.1 mm
Jacket - material	PVC



Technical Specifications

2. Shield braid - material	Alu
2. Shield braid - coverage %	77 %
3. Shield foil – material	Alu/PET

SHIELDING

Screening attenuation @ 1000-2000 MHz dB	≥ 95 dB
Screening attenuation @ 2000-3000 MHz dB	≥ 95 dB
Screening attenuation @ 30-1000 MHz dB	≥ 105 dB

TRANSFER IMPEDANCE

Transfer Impedance @ 5-30 MHz mΩ/m	≤ 5 mΩ/m
--------------------------------------	----------

CHARACTERISTICS

LOSS

Attenuation (20°C/100mtr) @ 1000 MHz dB	20.3 dB
Attenuation (20°C/100mtr) @ 100 MHz dB	6.5 dB
Attenuation (20°C/100mtr) @ 1350 MHz dB	23.6 dB
Attenuation (20°C/100mtr) @ 1600 MHz dB	26.2 dB
Attenuation (20°C/100mtr) @ 1750 MHz dB	27.3 dB
Attenuation (20°C/100mtr) @ 200 MHz dB	9.0 dB
Attenuation (20°C/100mtr) @ 2150 MHz dB	30.8 dB
Attenuation (20°C/100mtr) @ 2400 MHz dB	32.5 dB
Attenuation (20°C/100mtr) @ 3000 MHz dB	36.5 dB
Attenuation (20°C/100mtr) @ 470 MHz dB	13.5 dB
Attenuation (20°C/100mtr) @ 50 MHz dB	4.6 dB
Attenuation (20°C/100mtr) @ 5 MHz dB	1.9 dB
Attenuation (20°C/100mtr) @ 800 MHz dB	18.3 dB
Attenuation (20°C/100mtr) @ 862 MHz dB	18.8 dB

RETURN LOSS

Structural return loss @ 1000-2000 MHz dB	> 18 dB
Structural return loss @ 2000-3000 MHz dB	> 16 dB
Structural return loss @ 470-1000 MHz dB	> 20 dB
Structural return loss @ 5-470 MHz dB	> 23 dB

ELECTRICAL

Capacity pF/m	52 ± 2 pF/m
Impedance Ω	75 ± 3 Ω
Inner DC resistance Ω/km	≤ 21.5 Ω/km
Outer DC resistance Ω/km	<15 Ω/km
Velocity ratio %	83 ± 1 %

OPERATIONAL

Application	Indoor
Notified Body	0051



Technical Specifications

DoP number	TR0009
Screening Efficiency	EN50117 (Class A)
Fire Class	EN 50575 (Eca)
Suitable for	F-compression connector EX 6-49 NT Plus F-compression connector EX 6-49/83 F-compression connector CX3 7.0 QM (Quick-mount) with o-ring, 50 pcs. box F-compression connector CX3 4.9 SC short, 100 pcs. box F-twist on connector SFC 070 F-twist on connector SFC 045 KOSWI 3 IEC coax plug, angled, male KOKWI 3 IEC coax plug, angled, female KOS 3 IEC coax plug, male KOK 3 IEC coax plug, female IEC - Self Install plug 56/5.1, straight, male IEC - Self Install plug 56/5.1, straight, female IEC - Self Install plug 56/5.1, angle, male IEC - Self Install plug 56/5.1,
Suitable for	F-compression connector EX 6-49 NT Plus F-compression connector EX 6-49/83 F-compression connector CX3 7.0 QM (Quick-mount) with o-ring, 50 pcs. box F-compression connector CX3 4.9 SC short, 100 pcs. box F-twist on connector SFC 070 F-twist on connector SFC 045 KOSWI 3 IEC coax plug, angled, male KOKWI 3 IEC coax plug, angled, female KOS 3 IEC coax plug, male KOK 3 IEC coax plug, female IEC - Self Install plug 56/5.1, straight, male IEC - Self Install plug 56/5.1, straight, female IEC - Self Install plug 56/5.1, angle, male IEC - Self Install plug 56/5.1,

MECHANICAL

Cable length m	250 m
Colour	White
Packaging Depth m	0.340 m
Packaging Height m	0.170 m



TRIAx

connecting the future

Technical Specifications

Total Weight kg	0.043 kg
Packaging Width m	0.340 m
Minimum bending radius - single/repeated mm	35/70 mm
Net Weight kg	0.043 kg
Tara Weight kg	0.000 kg
Packaging Volume m3	0.000 m3